



| Gutter Size A & B | Maximum length | Spigot | Product Code |
|----------------------|-------------------|----------|--------------|
| 200 x 150mm | 3000mm | Internal | 86MOG3 |

Product Description

Extruded aluminium gutters are a fantastic option for new build and refurbishment applications due to their smooth lines, clean appearance and robust properties. This large profile can collect a considerable amount of rainwater run off and provide drainage for the largest all pitched roofs, like school and commercial buildings.

Properties

Made from aluminium alloy 6063 T6 and LM6
100% recyclable, lightweight and strong
Radius gutters - Faceted radius available
Other profiles available

Supplied Mill Finished (uncoated) or coated on ARP's in-house Polyester Powder Coating line to clients choice of RAL or BS standard colours.

Jointing

This gutter is jointed using loose internal unions and are bolted together for additional strength. Lengths are butt jointed, then a low modular sealant, such as Arbosil 1096, is applied and the union is then bolted to both sides creating a joint which will stand up to thermal movement.

For step by step instructions please refer to ARP product installation guide.

Functional Life Expectancy

ARP qualifies that when installed correctly and maintained in accordance with its product guidelines and O&M procedure, its products are designed to give a minimum effective functional life expectancy of 30 years.

Specification Information

Clause: R10/311 Rainwater Drainage Systems

Product: Sentinel Modern Ogee Gutter System

Manufacturer: ARP Ltd
Unit 2 Vitruvius Way
Meridian Business Park
Braunstone, Leicester
LE19 1WA

Handling & Storage

Gutters, downpipes and fittings, particularly with polyester powder coat finish should be handled with care and should preferably be stored under cover on racks to prevent scratching. All lengths are supplied in protective polythene wrapping, components suitably packed in boxes. If painted products are to be stored outside, cover with tarpaulin to guard against water ingress into the protective polythene. Mill finish items should be stored undercover to avoid uneven oxidation prior to being fitted.

Maintenance

In order to maintain proper working order, gutters should be periodically cleaned out and any built-up debris removed. Check all fixings are secure and take any remedial action to rectify if necessary. To maximise the life of the decorative paint finishes, all parts should be washed down with clean water at least every 12 months and any damage repaired. In marine/industrial environments, this period may need to be shortened to 6 months.

Further Information

Please visit www.arp-ltd.com or contact the ARP team of 0116 289 4400 for any other information